

Features

stable and can resist wind speeds of up to 20 m/s.

Modular design, modules and PSU offers both front and rear service access. Climbing steps are available for quick and easy

Platform Design

Different pixel modules can be used on one cabinet frame. The VNT's modules and PSU are also applicable to the VN series cabinet frames, an investment with multiple benefits.


Curveable

7.5° convex to 7.5° concave, 2.5°/unit 3 steps to set-up

Touring cart system

15-in-1 touring cart system. VNT touring cart fits perfectly into trucks, allowing 2 rows and 2 columns total 210sqm to fit in the 40HQ container.





Specifications

| VNT | VN-390T | VN-480T | VN-690T |
|-------------------------|-------------------|----------------------|-------------------|
| LEDType | SMD | SMD | SMD |
| Pixel Pitch | 3.9 mm | 4.8 mm | 6.9 mm |
| Max. Brightness | 5000 nit | 5000 nit | 5000 nit |
| Cabinet Material | | Die Casting Aluminum | |
| Cabinet Dimensions | 500x1000x130 mm | 500x1000x130 mm | 500x1000x130 mm |
| (LxWxD) | 19.69x39.37x5.11" | 19.69x39.37x5.11" | 19.69x39.37x5.11" |
| Cabinet Resolution(HxV) | 128x256 | 104x208 | 72x144 |
| Weight Per Cabinet | 15 Kg/33.06 lbs | 15 Kg/33.06 lbs | 15 Kg/33.06 lbs |
| Gray Scale | 14 bit | 14 bit | 14 bit |
| Refresh Rate | 3840 Hz | 3840 Hz | 3840 Hz |
| Viewing Angle(H/V) | 140°/140° | 140°/120° | 140°/120° |
| IP Rating (Front/Rear) | IP65/IP54 | IP65/IP54 | IP65/IP54 |
| Certificate | | CE, ETL, FCC | |